



econ strainers stainless steel

as above, however PN 63: fig. 1055
socket-welding ends PN 63: fig. 1056
flanged ends to PN 25: fig. 1046




fig. 1046



fig. 1055

pressure/temperature rating:

fig. 1046: 25 bar - 120 °C
13 bar - 400 °C

fig. 1055/1056: 63 bar - 120 °C
30 bar - 400 °C

materials:

	fig. 1055/1056	fig. 1046
body	forged stainless steel (Ws.no. 1.4404)	cast stainless steel (Ws.no. 1.4410)
cap/cover*	stainless steel (Ws.no. 1.4410)	stainless steel (Ws.no. 1.4404)
screen	stainless steel (Ws.no. 1.4401)	nickel

* DN ≥ 40 with bolted cover

screen perforations:

fig. 1055/1056 : 0.3 mm
fig. 1046 : 0.6 mm

on request:

- screen with other perforations
- flanged ends to other standards
- with permanent magnet

dimensions (mm):




fig. 1055




fig. 1056

fig. 1055/1056						drain size
D ₁	D ₂	E	L	H	wt (kg)	
21.8	31	8	86	60	0.6	1/4"
27.1	37	8	105	70	1.1	3/8"
34	45	11	120	90	1.7	1/2"
—	—	—	—	—	—	—
48.7	61	13	160	110	8	3/4"
61.1	75	16	200	140	12	1"




fig. 1046

fig. 1046						
DN	A	L	H	E	F	wt (kg)
15	95	130	67	57	23	2.4
20	105	150	79	69	28	3.2
25	115	160	111	83	36	4.8
32	140	180	130	99	42	6.8
40	150	200	143	115	50	8.2
50	165	230	175	154	60	11.8
65	185	290	216	187	76	18.2
80	200	310	235	201	83	23.2
100	235	350	274	265	105	36
125	270	400	311	310	130	50
150	300	480	353	340	155	74